

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** CARSYSTEM FLEX
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Not determined
- **Application of the substance / the mixture** Knife filler/ Surfacers
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Vosschemie GmbH
Esinger Steinweg 50
D-25436 Uetersen
Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de
- **Further information obtainable from:**
Abteilung Labor / +49 (0)4122 717 0
s.schaller@vosschemie.de
- **1.4 Emergency telephone number:**
Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland
Phone: +49 (0)551 19240

- **1.5 Distributed By:**

Sydney Automotive Paint and Equipment

Unit A3, 366 Edgar Street

Condell Park

NSW 2200

Australia

Tel: +61 2 9772 9000

Email: reception@sape.com.au

Emergency telephone: AU Poison Information Centre 13 11 26

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 1)

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

styrene

· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 2)

SECTION 3: Composition/information on ingredients· **3.2 Chemical characterisation: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	styrene ⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	10-<20%
CAS: 2687-91-4 EINECS: 220-250-6	1-ethylpyrrolidin-2-one ⚠ Repr. 1B, H360D	0.1-<0.3%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures**· **4.1 Description of first aid measures**· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

Call a doctor immediately.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**Hazchem: •3Y**· **5.1 Extinguishing media**· **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray.· **For safety reasons unsuitable extinguishing agents:** Water with full jet· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**· **Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 3)

· Additional information*Cool endangered receptacles with water spray.**Collect contaminated fire fighting water separately. It must not enter the sewage system.**Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.***SECTION 6: Accidental release measures****· 6.1 Personal precautions, protective equipment and emergency procedures***Wear protective equipment. Keep unprotected persons away.**Avoid contact with the eyes and skin.**Ensure adequate ventilation**Do not inhale gases / fumes / aerosols.**Keep away from ignition sources.***· 6.2 Environmental precautions:***Do not allow to enter sewers/ surface or ground water.**Inform respective authorities in case of seepage into water course or sewage system.***· 6.3 Methods and material for containment and cleaning up:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Do not flush with water or aqueous cleansing agents***· 6.4 Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***SECTION 7: Handling and storage****· 7.1 Precautions for safe handling***Keep receptacles tightly sealed.**Ensure good ventilation/exhaustion at the workplace.**Do not inhale gases / fumes / aerosols.**Avoid contact with the eyes and skin.***· Information about fire - and explosion protection:***Keep ignition sources away - Do not smoke.**Fumes can combine with air to form an explosive mixture.**Protect against electrostatic charges.**Use explosion-proof apparatus / fittings and spark-proof tools.**Ground/bond container and receiving equipment.***· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:** *Store only in the original receptacle.***· Information about storage in one common storage facility:***Store away from oxidising agents.**Store away from foodstuffs.***· Further information about storage conditions:***Store in cool, dry conditions in well sealed receptacles.**Store receptacle in a well ventilated area.**Protect from heat and direct sunlight.***· Recommended storage temperature:** *< 30 °C*

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 4)

· 7.3 *Specific end use(s)* No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

100-42-5 styrene

WEL (Great Britain)	Short-term value: 1080 mg/m ³ , 250 ppm Long-term value: 430 mg/m ³ , 100 ppm
---------------------	--

· **DNELs**

100-42-5 styrene

Oral	Long-term exposure - systemic effects	2.1 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	343 mg/kg bw/day (general population) 406 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	10.2 mg/m ³ (general population) 85 mg/m ³ (worker)
	Acute/short-term exposure - systemic effects	174.25 mg/m ³ (general population) 289 mg/m ³ (worker)
	Acute/short-term exposure - local effects	182.75 mg/m ³ (general population) 306 mg/m ³ (worker)

· **PNECs**

100-42-5 styrene

PNEC aqua	0.028 mg/l (freshwater)
	0.0028 mg/l (marine water)
	0.04 mg/l (intermittent releases)
PNEC sediment	0.614 mg/kg (freshwater)
	0.0614 mg/kg (marine water)
PNEC STP	5 mg/l
PNEC soil	0.2 mg/kg (soil dw)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- Wash hands before breaks and at the end of work.
- Keep away from foodstuffs, beverages and feed.
- Do not eat, drink, smoke or sniff while working.
- Store protective clothing separately.
- Immediately remove all soiled and contaminated clothing
- Take off contaminated clothing.
- Use skin protection cream for skin protection.

· **Respiratory protection:**

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 5)

Adhere to the workplace limit values and / or other threshold values.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check the permeability prior to each anewed use of the glove.

Preventive skin protection by use of skin-protecting agents is recommended.

Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove materialValue for the permeation: Level ≤ 6 (≥ 480 min)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not suitable are gloves made of the following materials:

Natural rubber, NR

Chloroprene rubber, CR

Nitrile rubber, NBR

Butyl rubber, BR

PVC gloves

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Pasty
Colour:	Dark grey
Odour:	Characteristic

pH-value: Not determined**Change in condition****Melting point/Melting range:** Undetermined.

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 6)

Boiling point/Boiling range:	145 °C
· Flash point:	31 °C
· Ignition temperature:	480 °C
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
· Vapour pressure at 20 °C:	6 hPa
· Density at 20 °C:	1.9 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No decomposition if used according to specifications.
- **10.2 Chemical stability** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with peroxides and other radical forming substances.
Exothermic polymerisation.
- **10.4 Conditions to avoid**
Protect from heat.
Avoid naked flames, sparks, other ignition sources and sunlight.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

100-42-5 styrene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD 50	>2000 mg/kg (rat) (OECD 402)
Inhalative	LC50 /4h	11.8 mg/l (rat)

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 7)

2687-91-4 1-ethylpyrrolidin-2-one

Oral	LD50	3200 mg/kg (rat) (OECD 401)
Dermal	LD 50	> 2000 mg/kg (rat) (OECD 402)
Inhalative	LC 50 / 4h	> 5.1 mg/l (rat) (OECD 403, Aerosol)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.

· **Subacute to chronic toxicity:****100-42-5 styrene**

Inhalative	NOAEL (subacute)	0.85 mg/l (rat) (13w, 6h/day, Vapour)
	NOAEL (subchronic)	0.8 mg/l (rat) (OECD 453, 2a, 6h/day, Vapour)

- **Additional toxicological information:**
May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Sensitisation** No sensitising effects known.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Suspected of damaging the unborn child.

· **Carcinogenicity****100-42-5 styrene**

Inhalative	NOAEL (carcinogenicity)	4.34 mg/l (rat) (OECD 453, 2a, 6h/day, 5d/week, Vapour)
------------	-------------------------	---

· **Reproductive toxicity/Fertility****100-42-5 styrene**

Inhalative	NOAEL (fertility)	0.65 mg/l (rat, parents) (OECD 416, Vapour)
		0.22 mg/l (rat, F2) (OECD 416, Vapour)
		2.2 mg/l (rat) (OECD 416, Parents, Vapour)

· **Reproductive toxicity/Teratogenicity****100-42-5 styrene**

Inhalative	NOAEL (developmental toxicity)	2.6 mg/l (rat)
	NOAEL (teratogenicity)	2.6 mg/l (rat)
	LOAEL (maternally)	1.3 mg/l (rat)

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

-GB-

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 8)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

100-42-5 styrene

EC10/96h 0.28 mg/l (*Pseudokirchneriella subcapitata*) (EPA OTS 797.1050)

EC50/48h 4.7 mg/l (*daphnia magna*) (OECD 202)

EC50/72h 4.9 mg/l (*Pseudokirchneriella subcapitata*) (EPA OTS 797.1050)

EC50/0.5h ≈ 500 mg/l (activated sludge) (OECD 209)

LC50/96h 4.02 mg/l (*pimephales promelas*)

NOEC 1.01 mg/l (*daphnia magna*) (OECD-211 21d)

2687-91-4 1-ethylpyrrolidin-2-one

EC50/48h > 104 mg/l (*daphnia*) (OECD 202)

EC50/72h > 101 mg/l (*desmodesmus subspicatus*) (OECD 201)

NOEC 12.5 mg/l (*daphnia*) (OECD 211, 21d)

· 12.2 Persistence and degradability

100-42-5 styrene

Biodegradation 70.9 % (activated sludge) (ISO DIN 9408, 28d, aerob)

· 12.3 Bioaccumulative potential

100-42-5 styrene

log Kow 2.95

BCF 74 (calculated)

13.5 (fish)

· Behaviour in environmental systems:

· 12.4 Mobility in soil

100-42-5 styrene

log Koc 2.55

Koc 352

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 9)

· **Waste disposal key:**
The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

· **European waste catalogue**

07 02 08* | other still bottoms and reaction residues

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**
· **ADR, IMDG, IATA** UN1866

· **14.2 UN proper shipping name**
· **ADR** 1866 RESIN SOLUTION
· **IMDG, IATA** RESIN SOLUTION

· **14.3 Transport hazard class(es)** **Hazchem: •3Y**
· **ADR**



· **Class** 3 Flammable liquids.
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.

· **14.4 Packing group**
· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Warning: Flammable liquids.
· **EMS Number:** F-E,S-D

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**
· **Limited quantities (LQ)** 5L
· **Transport category** 3
· **Tunnel restriction code** D/E
· **Remarks:** ADR 2.2.3.1.5

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 10)

- **IMDG**
- **Remarks:** IMDG-Code 2.3.2.5

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **European regulations**
- **Directive 2004/42/EC 2004/42/IIB (b) (250) <250**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **National regulations:**
- **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- **Other regulations, limitations and prohibitive regulations**
Adhere to the Ordinances on the Prohibition of Certain Chemicals.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H360D May damage the unborn child.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.
- H412 Harmful to aquatic life with long lasting effects.
- **Department issuing SDS:** Abteilung Labor
- **Contact:** Frau S. Schaller
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.06.2017

V - 4

Revision: 06.06.2017

Trade name: CARSYSTEM FLEX

(Contd. of page 11)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
SVHC: Substances of Very High Concern
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

GB

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BPO-Härter rot

Product code : 132.413

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Curing chemical

1.3 Details of the supplier of the safety data sheet

Company : A.Förster & Co.KG
Esinger Steinweg 50
25436 Uetersen
Germany
info@foerster-co.de

Telephone : 04122-3682

Responsible Department : Laboratory

04122-3682
info@foerster-co.de

1.4 Emergency telephone number

Telephone : POISONS INFORMATION CENTRE
Australia

13 11 26

1.5 Details of the supplier/importer

Company : Sydney Automotive Paints and Equipment
Unit A3, 366 Edgar Street
Condell Park, 2200

reception@sape.com.au

Telephone : 02 9772 9000
Telefax : 02 9772 9001

Responsible Department : Marketing
02 9772 9000

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

A. Förster
& CO.KG

BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type E	H242: Heating may cause a fire.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.
P234 Keep only in original packaging.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if pre-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

sent and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P410 Protect from sunlight.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label:

dibenzoyl peroxide

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture
contains
Organic Peroxide

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
dibenzoyl peroxide	94-36-0 202-327-6 617-008-00-0 01-2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M factor (acute) = 10 M factor (chronic) = 10	>= 45 - < 55
ethanediol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373	>= 1 - < 10

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

A. Förster
& CO.KG

BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Show this safety data sheet to the doctor in attendance.
First aider needs to protect himself.
- If inhaled : Move to fresh air.
Get medical attention.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Call a physician if irritation persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
Remove contact lenses.
Consult a physician.
- If swallowed : Rinse mouth with water.
Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

Hazchem: 1W

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Hazardous decomposition products formed under fire conditions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.
- Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Wear personal protective equipment. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Do not smoke. Avoid contact with skin, eyes and clothing. In the case of vapour formation use a respirator with an approved filter.

6.2 Environmental precautions

- Environmental precautions : Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.
- Advice on safe handling : Use only with adequate ventilation. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Keep away from heat and sources of ignition. Handle and open container with care. Keep container tightly closed and dry. Never return unused material to storage receptacle.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

Risk of decomposition.
Prevent contamination with readily oxidizable materials and polymerisation accelerators.
Avoid inhalation of vapour or mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid release to the environment.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.
Keep away from open flames, hot surfaces and sources of ignition.
Keep away from direct sunlight.
Avoid shock and friction.
Take measures to prevent the build up of electrostatic charge.
Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container.
Avoid letting the product become dry.
Keep containers tightly closed in a cool, well-ventilated place.
Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

Advice on common storage : Keep away from food, drink and animal feedingstuffs.
Keep away from reducing agents.
Incompatible with acids and bases.
Heavy metal compounds

Recommended storage temperature : ≤ 25 °C

7.3 Specific end use(s)

Specific use(s) : No data available
The rules which cover amongst other things the requirement for ventilation, protective clothing, personal protective equipment etc. can be obtained from the National Occupational Health and Safety Board.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dibenzoyl peroxide	94-36-0	TWA	5 mg/m ³	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
dimethyl phthalate	131-11-3	TWA	5 mg/m ³	GB EH40
		STEL	10 mg/m ³	GB EH40
ethanediol	107-21-1	STEL	40 ppm	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version
1.1

GB/EN

Revision Date:
29.10.2019

Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

			104 mg/m ³	
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 52 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA (Vapour)	20 ppm 52 mg/m ³	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA (particles)	10 mg/m ³	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL (Vapour)	40 ppm 104 mg/m ³	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
dibenzoyl peroxide	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	13.3 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	39 mg/m ³
ethanediol	Workers	Inhalation	Long-term local effects	35 mg/m ³
	Workers	Dermal	Long-term systemic effects	106 mg/kg
	Consumers	Inhalation	Long-term local effects	7 mg/m ³
	Consumers	Dermal	Long-term systemic effects	53 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dibenzoyl peroxide	Fresh water	0.00002 mg/l
	Intermittent use/release	0.000602 mg/l
	Marine water	0.000002 mg/l
	Fresh water sediment	0.0127 mg/kg dry weight (d.w.)
	Marine sediment	0.00127 mg/kg dry weight (d.w.)
	Soil	0.0025 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.35 mg/l
ethanediol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Sewage treatment plant	199.5 mg/l
	Fresh water sediment	37 mg/kg
	Marine sediment	3.7 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Neoprene gloves

Material : Nitrile rubber

Break through time : > 30 min

Glove thickness : ≥ 0.14 mm

Directive : DIN EN 374

Protective index : Class 2

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

In case of inadequate ventilation wear respiratory protection.

Filter type : Combined particulates and organic vapour type (A-P)

Protective measures : When using do not eat, drink or smoke.
Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

BPO-Härter rot

Version	Revision Date:	Date of last issue: 05.04.2019
1.1	29.10.2019	Date of first issue: 05.04.2019

Appearance	: paste
Colour	: red
Odour	: characteristic
Melting point/range	: not determined
Boiling point/boiling range	: not determined
Flash point	: Not applicable, Decomposition
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Vapour pressure	: not determined
Density	: 1.15 - 1.25 g/cm ³ (20 °C)
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Viscosity Viscosity, kinematic	: not determined
Oxidizing properties	: Organic peroxide Sustains combustion

9.2 Other information

Self-Accelerating decomposition temperature (SADT)	: 50 °C
Peroxide content	: 50 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	: Risk of decomposition. Reacts violently in contact with acids, amines, driers, polymer-
---------------------	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version	Revision Date:	Date of last issue: 05.04.2019
1.1	29.10.2019	Date of first issue: 05.04.2019

isation accelerators and easily oxidized materials.

10.4 Conditions to avoid

Conditions to avoid : Do not expose to temperatures above: > 25 °C
Extremes of temperature and direct sunlight.
Keep away from heat and sources of ignition.
Contact with incompatible substances can cause decomposition at or below SADT.

10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

dibenzoyl peroxide:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 24.3 mg/l
Exposure time: 4 h

ethanediol:

Acute oral toxicity : Acute toxicity estimate: 500.0 mg/kg
Method: Converted acute toxicity point estimate

Acute inhalation toxicity : LC50 (Rat): > 2.5 mg/l
Exposure time: 6 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Mouse): > 3,500 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

ethanediol:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

ethanediol:

No aspiration toxicity classification

SECTION 12: Ecological information

12.1 Toxicity

Components:

dibenzoyl peroxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.0602 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

NOEC (Fish): 0.0316 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.11 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 0.0711 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.02 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 10

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 0.001 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 10

ethanediol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 72,860 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : NOEC (algae): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 15,380 mg/l
Exposure time: 28 d
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: \geq 1,000 mg/l
Exposure time: 23 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not mix waste streams during collection.
Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
16 05 06, laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals
16 09 03, peroxides, for example hydrogen peroxide

SECTION 14: Transport information

14.1 UN number

ADN : UN 3108
ADR : UN 3108
RID : UN 3108
IMDG : UN 3108
IATA : UN 3108

14.2 UN proper shipping name

ADN : ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
ADR : ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
RID : ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

IMDG : ORGANIC PEROXIDE TYPE E, SOLID
(dibenzoyl peroxide)

IATA : Organic peroxide type E, solid
(dibenzoyl peroxide)

14.3 Transport hazard class(es)

ADN : 5.2

ADR : 5.2

RID : 5.2

IMDG : 5.2

IATA : 5.2

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : P1
Labels : 5.2

ADR
Packing group : Not assigned by regulation
Classification Code : P1
Labels : 5.2
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : P1
Hazard Identification Number : 539
Labels : 5.2

IMDG
Packing group : Not assigned by regulation
Labels : 5.2
EmS Code : F-J, S-R

IATA (Cargo)
Packing instruction (cargo aircraft) : 570
Packing group : Not assigned by regulation
Labels : Division 5.2 - Organic peroxides, Handling Label - Keep Away From Heat

IATA (Passenger)
Packing instruction (passenger aircraft) : 570
Packing group : Not assigned by regulation
Labels : Division 5.2 - Organic peroxides, Handling Label - Keep Away From Heat

14.5 Environmental hazards

ADN
Environmentally hazardous : no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version	Revision Date:	Date of last issue: 05.04.2019
1.1	GB/EN 29.10.2019	Date of first issue: 05.04.2019

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : yes

Hazchem: 1W

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 ENVIRONMENTAL HAZARDS

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1 GB/EN Revision Date: 29.10.2019 Date of last issue: 05.04.2019
Date of first issue: 05.04.2019

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H241 : Heating may cause a fire or explosion.
H302 : Harmful if swallowed.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Irrit. : Eye irritation
Org. Perox. : Organic peroxides
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version	Revision Date:	Date of last issue: 05.04.2019
1.1	29.10.2019	Date of first issue: 05.04.2019

Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Org. Perox. E	H242
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.